

## AGRIMAX RT 600 - Ficha técnica

### Description

AGRIMAX RT 600 es el neumático ideal para utilizarlo en cubiertas herbáceas y actividades de cosecha y pulverización. Gracias a su amplia área de contacto, AGRIMAX RT 600 garantiza una óptima distribución de la presión sobre el terreno reduciendo los daños de prados y protege el suelo. Gracias a la tecnología con hombro redundado, la banda de rodamiento reforzada y el número mayor de tacos, el neumático asegura una grande estabilidad y excelente tracción.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cosechadora • Esparcidor • Tractor



SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>620/75 R 26 (23.1 R 26)</b>	STANDARD	94050444	167 A8/B	DW 20 B		24.6	62.6	28.7	191	TL	E11-106R-002993
<b>750/65 R 26</b>	STANDARD	94064311	171 A8/B	DW 24 B	DW 23 B ; DW 25 B	29.5	64.4	29	196.3	TL	E11-106R-006182
<b>750/70 R 26</b>	STANDARD	94073146	172 A8/B	DW 25 B	DW 24 B	30.7	68.9	30.9	207.4	TL	E11-106R-007934
<b>540/65 R 28</b>	STANDARD	94053704	142 D/145 A8	W 16 L	W 18 L	20.9	55.6	25.3	165.4	TL	E11-106R-002980
<b>1050/50 R32</b>	STANDARD	94040728	184 A8/181 B	36.0 VA		41.7	73.3	32.5	224.4	TL	E4-106R-000813
<b>650/75 R 32</b>	STANDARD	94055968	172 A8/B	DW 21 B	DW 20 B ; DW 23 B	25.8	70.4	31.8	213.2	TL	E11-106R-004755
<b>800/65 R 32 (30.5L R 32)</b>	STANDARD	94044795	176 A8/173 B	DW 27 B	DH 27 B ; DW 25 B	30.5	71.7	32.4	218.8	TL	E4-106R-001428
<b>800/65 R 32 (30.5L R 32)</b>	STANDARD	94039302	181 A8/178 B	DW 27 B	DH 27 B ; DW 25 B	30.5	71.7	32.4	218.8	TL	E4-106R-001429
<b>900/60 R 32</b>	STANDARD	94062423	181 A8/178 B	DW 27 B	DW 28 B ; DW 30 B	35.3	74.5	33.1	224.3	TL	E11-106R-005768
<b>IF 1250/50 R 32 CFO</b>	STEEL BELTED	94070763	201 B	VA44/1.7 (multipiece)		49.1	81.2	35.3	241.6	TL	E11-106R-006958
<b>IF 1250/50 R 32 CFO</b>	STEEL BELTED	94068876	201 B	DH44B/1.3 (multipiece)		49.1	81.2	35.3	241.6	TL	E11-106R-006958
<b>IF 680/85 R 32 CFO</b>	STANDARD	94065486	179 D	DW23 B	DW21 B	26.9	77.2	33.3	230.7	TL	E11-106R-006401
<b>650/65 R 38</b>	STANDARD	94053667	157 D/160 A8	DW 20 B		25.4	71.3	32.8	214.3	TL	E11-106R-002990
<b>710/70 R 38</b>	STANDARD	94063420	178 D/181 A8	DW 23 B	DW 25 B	27.8	77.1	34.7	233.3	TL	E11-106R-006178

Printed on 23/04/2024 6:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..