

AGRIMAX RT 657 - Especificaciones técnicas



Description

AGRIMAX RT 657 es el neumático ideal para utilizarlo tanto en el laboreo del suelo como por la carretera; además algunos tamaños también son adecuados para la vendimia. Este neumático asegura un excelente confort en la conducción, así como significativos ahorros de carburante. Presenta una elevada capacidad de carga a altas velocidades. AGRIMAX RT 657 es la mejor elección para quien necesite un neumático versátil y fiable sin comprometer las prestaciones.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	540/65 R 28
LI/SS	149 D/152 A8

Dimensions US Standard

Usa code	94056927
Section Width (inch)	20.9
Overall Diameter (inch)	55.6
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	167.4
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000650
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3440	4010	4520	5020	5520	5950	6590	7150
30	3620	4220	4750	5280	5800	6250	6930	7530
25	3760	4390	4940	5480	6030	6500	7210	7830
20	3970	4620	5200	5780	6350	6840	7590	8240
5 LT	4620	5380	6050	6720	7400	7970	8840	9600
5 HT	3970	4620	5200	5780	6350	6840	7590	8240

Printed on 18/04/2024 11:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..