

AGRIMAX RT 657 - Especificaciones técnicas



Description

AGRIMAX RT 657 es el neumático ideal para utilizarlo tanto en el laboreo del suelo como por la carretera; además algunos tamaños también son adecuados para la vendimia. Este neumático asegura un excelente confort en la conducción, así como significativos ahorros de carburante. Presenta una elevada capacidad de carga a altas velocidades. AGRIMAX RT 657 es la mejor elección para quien necesite un neumático versátil y fiable sin comprometer las prestaciones.

UM

International Standard

Construction

RADIAL

Machinery

Agricultura: Tractor , Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	900/55 R 38
LI/SS	179 D/181 A8

Dimensions International Standard

Section Width (mm)	880
Overall Diameter (mm)	1950
Static Loaded Radius (mm)	880
Rolling Circumference (mm)	5842
SRI (mm)	925
Rim Rec	DW 27 B
Rim Alt	DW 30 B
ECE	E11-106R-006946
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8
65	3255	3800	4265	4805	5350	5890	6590	7055	7750
50	3420	3990	4480	5050	5620	6190	6920	7410	8140
40	3465	4045	4540	5115	5695	6270	7015	7510	8250
30	3745	4370	4905	5530	6155	6780	7580	8115	8915
10 LT	4365	5090	5715	6440	7170	7895	8830	9455	10385
10 HT	3745	4370	4905	5530	6155	6780	7580	8115	8915

Printed on 26/11/2022 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..