

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	320/70 R 24
LI/SS	116 D

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1094
Static Loaded Radius (mm)	502
Rolling Circumference (mm)	3245
SRI (mm)	525
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-005827
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	690	800	915	1025	1140	1250
50	725	845	960	1080	1200	1315
40	755	880	1005	1125	1250	1370
30	795	925	1055	1185	1315	1440
10 LT	925	1075	1225	1375	1525	1675
10 HT	795	925	1055	1185	1315	1440

Printed on 20/04/2024 14:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..