

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	360/70 R24
LI/SS	122 D

Dimensions International Standard

Section Width (mm)	357
Overall Diameter (mm)	1152
Static Loaded Radius (mm)	519
Rolling Circumference (mm)	3395
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E11-106R-005824
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	825	960	1095	1230	1365	1500
50	870	1010	1150	1295	1435	1575
40	905	1055	1205	1350	1500	1645
30	950	1105	1260	1415	1570	1725
10 LT	1110	1290	1470	1650	1830	2010
10 HT	950	1105	1260	1415	1570	1725

Printed on 20/04/2024 5:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..