

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	480/70 R 24
LI/SS	138 D

Dimensions US Standard

Usa code	94062195
Section Width (inch)	18.9
Overall Diameter (inch)	51.8
Static Loaded Radius (inch)	22.8
Rolling Circumference (inch)	153.3
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005519
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	2870	3340	3800	4280	4740	5200
30	3010	3510	4000	4490	4980	5470
25	3140	3650	4170	4670	5190	5700
20	3300	3840	4380	4920	5460	5990
5 LT	3850	4480	5100	5730	6360	6980
5 HT	3300	3840	4380	4920	5460	5990

Printed on 20/04/2024 15:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..