

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	480/70 R 34
LI/SS	155 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	728
Rolling Circumference (mm)	4788
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005834
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	1515	1785	2055	2290	2560	2790	3065	3295	3605	3875
50	1590	1875	2160	2405	2690	2935	3220	3460	3790	4070
40	1660	1955	2250	2505	2805	3060	3355	3610	3950	4245
30	1740	2055	2365	2635	2945	3215	3525	3795	4150	4460
10 LT	2030	2390	2755	3070	3430	3745	4105	4420	4835	5195
10 HT	1740	2055	2365	2635	2945	3215	3525	3795	4150	4460

Printed on 20/04/2024 12:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..