

AGRIMAX RT 765 - Especificaciones técnicas



Description

AGRIMAX RT 765, un neumático de la serie 70 de BKT, es ideal para equipar los tractores más modernos que se utilizan en los trabajos pesados, como el laboreo del suelo, el transporte tanto en el campo como por la carretera, la vendimia y la pulverización. Su amplia área de contacto garantiza una mejor tracción y excelente confort en todas las superficies y en cualquier momento. Este neumático proporciona optimas propiedades de auto-limpieza y una reducida compactación del suelo. Está disponible en dos tamaños con tecnología de cinturones de acero.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	620/70 R 46
LI/SS	162 D

Dimensions International Standard

TKPH	1
Section Width (mm)	625
Overall Diameter (mm)	2036
Static Loaded Radius (mm)	924
Rolling Circumference (mm)	6106
SRI (mm)	975
Rim Rec	DW 20 B
ECE	E11-106R-005999
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2615	3040	3470	3895	4325	4750
50	2745	3195	3645	4095	4545	4990
40	2865	3335	3800	4270	4740	5205
30	3010	3500	3990	4485	4975	5465
10 LT	3505	4075	4650	5220	5795	6365
10 HT	3010	3500	3990	4485	4975	5465

Printed on 20/04/2024 6:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..