

AGRIMAX RT 855 - Especificaciones técnicas



Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	320/85 R 20 (12.4 R 20)
LI/SS	119 A8/B

Dimensions US Standard

Usa code	94021963
Section Width (inch)	13
Overall Diameter (inch)	41.4
Static Loaded Radius (inch)	18.4
Rolling Circumference (inch)	122
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000645
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1650	1930	2190	2470	2730	3000
25	1650	1930	2190	2470	2730	3000
20	1770	2060	2360	2650	2930	3220
5 LT	2220	2580	2940	3310	3670	4020
5 HT	1770	2060	2360	2650	2930	3220

Printed on 25/04/2024 21:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..