

AGRIMAX RT 855 - Especificaciones técnicas



Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 28 (12.4 R 28)
LI/SS	124 A8/B

Dimensions US Standard

Usa code	94047352
Section Width (inch)	13
Overall Diameter (inch)	49.4
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	147.4
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000615
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3520
25	1940	2260	2580	2900	3220	3520
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780

Printed on 25/04/2024 16:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..