

## AGRIMAX RT 855 - Especificaciones técnicas



### Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	420/80 R 46 (16.9 R 46)
LI/SS	159 D/170 A2

## Dimensions US Standard

Usa code	94062065
TMPH	1
Section Width (inch)	16.5
Overall Diameter (inch)	72.4
Static Loaded Radius (inch)	34
Rolling Circumference (inch)	222.1
Rim Rec	W 13
Rim Alt	W 12
ECE	E4-106R-001489
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
40	3580	4110	4720	5320	5940	6550	7080	7610	8970	9640
30	3760	4320	4960	5600	6240	6880	7440	7990	9420	10130
25	3920	4510	5170	5840	6500	7180	7760	8330	9830	10570
20	4120	4730	5430	6130	6830	7530	8150	8750	10330	11100
5	4930	5650	6490	7330	8170	9010	9740	10470	12300	13230
5 LT	4790	5510	6330	7140	7960	8770	9490	10200	12030	12930
5 HT	4120	4730	5430	6130	6830	7530	8150	8750	10330	11100

Printed on 25/04/2024 17:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..