

## AGRIMAX RT 855 - Especificaciones técnicas



### Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	460/85 R 30 (18.4 R 30)
LI/SS	145 A8/B

## Dimensions US Standard

Usa code	94046775
Section Width (inch)	18.7
Overall Diameter (inch)	60.8
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	179.6
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E4-106R-000774
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3520	4100	4670	5250	5820	6390
25	3520	4100	4670	5250	5820	6390
20	3770	4390	5000	5620	6240	6840
5 LT	4720	5490	6260	7030	7800	8580
5 HT	3770	4290	5000	5620	6240	6840

Printed on 25/04/2024 20:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..