

## AGRIMAX RT 955 - Especificaciones técnicas



### Description

AGRIMAX RT 955 es un neumático radial BKT, ideal para las aplicaciones de cultivos en hilera, mientras que algunos tamaños son idóneos también para las actividades de pulverización y los viñedos. El dibujo de la banda de rodamiento con su hombro redondeado garantiza excelentes prestaciones de tracción, estabilidad y propiedades de auto-limpieza. Gracias a la carcasa robusta, AGRIMAX RT 955 ofrece una capacidad de carga elevada.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	270/80 R 36
LI/SS	134 A8/B

## Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1346
Static Loaded Radius (mm)	629
Rolling Circumference (mm)	4090
SRI (mm)	650
Rim Rec	W9
Rim Alt	W8; W10
ECE	E11-106R-006758
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	745	870	1000	1125	1255	1360	1510	1590	1740	1890	2015	2120
40	745	870	1000	1125	1255	1360	1510	1590	1740	1890	2015	2120
30	795	935	1070	1205	1340	1455	1615	1705	1865	2025	2160	2270
10	1115	1305	1495	1690	1880	2040	2260	2385	2610	2835	3025	3180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/02/2025 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..