

AGRIMAX RT 955 - Especificaciones técnicas



Description

AGRIMAX RT 955 es un neumático radial BKT, ideal para las aplicaciones de cultivos en hilera, mientras que algunos tamaños son idóneos también para las actividades de pulverización y los viñedos. El dibujo de la banda de rodamiento con su hombro redondeado garantiza excelentes prestaciones de tracción, estabilidad y propiedades de auto-limpieza. Gracias a la carcasa robusta, AGRIMAX RT 955 ofrece una capacidad de carga elevada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	270/95 R 48 (11.2 R 48)
LI/SS	144 A8/B

Dimensions International Standard

Section Width (mm)	275
Overall Diameter (mm)	1733
Static Loaded Radius (mm)	820
Rolling Circumference (mm)	5351
SRI (mm)	825
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000782
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1095	1430	1740	1905	2020	2215	2410	2605	2800	-
40	1095	1430	1740	1905	2020	2215	2410	2605	2800	-
30	1170	1530	1860	2040	2160	2370	2580	2790	3000	-
10	1305	1640	2020	2395	2775	2860	3195	3530	3865	4200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/02/2025 16:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..