

AGRIMAX RT 955 - Ficha técnica

Description

AGRIMAX RT 955 es un neumático radial BKT, ideal para las aplicaciones de cultivos en hilera, mientras que algunos tamaños son idóneos también para las actividades de pulverización y los viñedos. El dibujo de la banda de rodadura con su hombro redondeado garantiza excelentes prestaciones de tracción, estabilidad y propiedades de auto-limpieza. Gracias a la carcasa robusta, AGRIMAX RT 955 ofrece una capacidad de carga elevada.

UM

International Standard

Construction

RADIAL

Machinery

Agricultura: Pulverizador, Vendimiadora



| SIZE | Version | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|----------------------------|----------|----------|------------|---------|-----------------------------|-----|------|-----|------|-----|------|-----------------|
| 210/90 R 24 (8.3 R 24) | STANDARD | R1 | 107 A8/B | W 7 | W 6 | 214 | 1010 | 462 | 3027 | 475 | TL | E4-106R-001818 |
| 210/95 R 28 (8.3 R 28) | STANDARD | R1 | 116 A8/B | W 7 | W 6 | 214 | 1111 | 513 | 3333 | 550 | TL | E4-106R-001819 |
| 210/95 R 32 (8.3 R 32) | STANDARD | R1 | 120 A8/B | W 7 | W 6 | 214 | 1213 | 571 | 3703 | 575 | TL | E4-106R-001391 |
| 230/95 R 32 (9.5 R 32) | STANDARD | R1 | 128 A8/B | W 7 | W 8 | 228 | 1251 | 585 | 3810 | 600 | TL | E4-106R-000764 |
| 270/95 R 32 (11.2 R 32) | STANDARD | R1 | 136 A8/B | W 9 | W 8 ; W 10 | 275 | 1327 | 614 | 4076 | 625 | TL | E4-106R-000776 |
| 230/95 R 36 (9.5 R 36) | STANDARD | R1 | 130 A8/B | W 8 | W 7 | 238 | 1352 | 639 | 4112 | 650 | TL | E4-106R-000765 |
| 270/80 R 36 | STANDARD | R1 | 134 A8/B | W9 | W8; W10 | 275 | 1346 | 629 | 4090 | 650 | TL | E11-106R-006758 |
| 270/95 R 36 (11.2 R 36) | STANDARD | R1 | 139 A8/B | W 9 | W 8 ; W 10 | 275 | 1428 | 665 | 4368 | 675 | TL | E4-106R-000659 |
| 270/95 R 38 (11.2 R 38) | STANDARD | R1 | 140 A8/B | W 9 | W 8 ; W 10 | 275 | 1479 | 697 | 4510 | 700 | TL | E4-106R-000657 |
| 230/95 R 40 (9.5 R 40) | STANDARD | R1 | 132 A8/B | W 7 | W 8 | 228 | 1454 | 690 | 4445 | 700 | TL | E11-106R-004066 |
| 230/95 R 42 (9.5 R 42) | STANDARD | R1 | 133 A8/B | W 8 | W 7 | 238 | 1506 | 714 | 4595 | 725 | TL | E4-106R-000772 |
| 300/85 R 42 (11.2 R 42) | STANDARD | R1 | 144 A8/B | W 9 | W 10 ; W 11 | 295 | 1577 | 745 | 4850 | 750 | TL | E4-106R-001396 |
| 210/95 R 44 (8.3 R 44) | STANDARD | R1 | 120 A8/B | W 7 | W 6 | 214 | 1518 | 721 | 4653 | 725 | TL | E4-106R-000771 |
| 230/95 R 44 (9.5 R 44) | STANDARD | R1 | 134 A8/B | W 8 | W 7 | 238 | 1556 | 739 | 4788 | 750 | TL | E4-106R-000777 |
| 270/95 R 44 (11.2 R 44) | STANDARD | R1 | 142 A8/B | W 9 | W 8 ; W 10 | 275 | 1632 | 764 | 4983 | 775 | TL | E4-106R-00784 |
| 270/95 R 46 (11.2 R 46) | STANDARD | R1 | 143 A8/B | W 9 | W 8 ; W 10 | 275 | 1683 | 792 | 5169 | 825 | TL | E4-106R-000785 |
| 300/95 R 46 (12.4 R 46) | STANDARD | R1 | 148 A8/B | W 9 | W 10 ; W 11 ; DW 10 ; DW 11 | 295 | 1738 | 812 | 5318 | 850 | TL | E4-106R-000790 |
| 340/85 R 46 (13.6 R 46) | STANDARD | R1 | 150 A8/B | W 12 | W 11 | 353 | 1746 | 826 | 5346 | 850 | TL | E4-106R-001828 |
| 230/95 R 48 (9.5 R 48) | STANDARD | R1 | 136 A8/B | W 8 | W 7 | 238 | 1656 | 792 | 5085 | 825 | TL | E4-106R-000778 |
| 230/95 R 48 (9.5 R 48) | STANDARD | R1 | 136D/139A8 | W 8 | W 7 | 238 | 1656 | 792 | 5085 | 825 | TL | E11-106R-004067 |
| 270/95 R 48 (11.2 R 48) | STANDARD | R1 | 144 A8/B | W 9 | W 8 ; W 10 | 275 | 1733 | 820 | 5351 | 850 | TL | E4-106R-000782 |
| 340/85 R 48 (13.6 R 48) | STANDARD | R1 | 152 A8/B | W 12 | W 11 | 353 | 1797 | 855 | 5572 | 875 | TL | E4-106R-000800 |
| 300/95 R 52 (12.4 R 52) | STANDARD | R1 | 151 A8/B | W 9 | W 10 ; W 11 ; DW 10 ; DW 11 | 295 | 1891 | 889 | 5774 | 925 | TL | E4-106R-001484 |
| 270/95 R 54 (11.2 R 54) | STANDARD | R1 | 146 A8/B | W 9 | W 8 ; W 10 | 275 | 1885 | 894 | 5815 | 925 | TL | E4-106R-001410 |

Printed on 26/11/2022 17:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..