

## AGRIMAX SIRIO - Especificaciones técnicas



### Description

AGRIMAX SIRIO es un neumático para las altas velocidades (hasta 70 km/h) desarrollado por BKT para equipar los tractores de elevada potencia. El dibujo es perfecto para las aplicaciones de transporte y tratamiento del terreno. La elevada flexibilidad del flanco asegura una estabilidad, manutención y confort extraordinarios, mejorando la experiencia de conducir. Esta también disponible con tecnología IF permitiendo el transporte de cargas pesadas a baja presión. La carcasa reforzada y el número alto de cinturones garantizan una excelente tracción en el campo, mientras que la baja resistencia al rodamiento contribuye a un consumo menor de carburante.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor de alta potencia

Version	HIGH SPEED
Type	TL
Tyre Size	540/65 R 30
LI/SS	150 D/147 E

## Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1464
Static Loaded Radius (mm)	669
Rolling Circumference (mm)	4400
SRI (mm)	700
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E4-106R-000814
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1450	1665	1910	2155	2400	2645	2860	3075
65	1575	1810	2080	2345	2615	2885	3120	3350
50	1655	1905	2185	2465	3750	3030	3275	3520
40	1725	1985	2280	2570	2865	3160	3415	3670
25	1870	2145	2465	2780	3100	3415	3695	3970
10	2365	2715	3120	3520	3920	4325	4675	5025

Printed on 06/12/2023 21:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..