

AGRIMAX SIRIO - Especificaciones técnicas



Description

AGRIMAX SIRIO es un neumático para las altas velocidades (hasta 70 km/h) desarrollado por BKT para equipar los tractores de elevada potencia. El dibujo es perfecto para las aplicaciones de transporte y tratamiento del terreno. La elevada flexibilidad del flanco asegura una estabilidad, manutención y confort extraordinarios, mejorando la experiencia de conducir. Esta también disponible con tecnología IF permitiendo el transporte de cargas pesadas a baja presión. La carcasa reforzada y el número alto de cinturones garantizan una excelente tracción en el campo, mientras que la baja resistencia al rodamiento contribuye a un consumo menor de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	HIGH SPEED
Type	TL
Tyre Size	540/65 R 34
LI/SS	152 D/149 E

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1566
Static Loaded Radius (mm)	721
Rolling Circumference (mm)	4735
SRI (mm)	750
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E4-106R-000815
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1530	1755	2015	2275	2535	2795	3025	3250
65	1670	1920	2205	2485	2770	3055	3305	3550
50	1755	2015	2315	2615	2910	3210	3470	3730
40	1830	2105	2415	2725	3035	3350	3620	3890
25	1980	2275	2615	2950	3285	3625	3920	4210
10	2505	2880	3305	3730	4155	4580	4955	5325

Printed on 23/04/2024 17:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..