

AGRIMAX SIRIO - Especificaciones técnicas



Description

AGRIMAX SIRIO es un neumático para las altas velocidades (hasta 70 km/h) desarrollado por BKT para equipar los tractores de elevada potencia. El dibujo es perfecto para las aplicaciones de transporte y tratamiento del terreno. La elevada flexibilidad del flanco asegura una estabilidad, manutención y confort extraordinarios, mejorando la experiencia de conducir. Esta también disponible con tecnología IF permitiendo el transporte de cargas pesadas a baja presión. La carcasa reforzada y el número alto de cinturones garantizan una excelente tracción en el campo, mientras que la baja resistencia al rodamiento contribuye a un consumo menor de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	HIGH SPEED
Type	TL
Tyre Size	540/65 R 38
LI/SS	153 D/150 E

Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1667
Static Loaded Radius (mm)	769
Rolling Circumference (mm)	5050
SRI (mm)	800
Rim Rec	W 16 L
Rim Alt	W 18 L
ECE	E4-106R-000816
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1575	1810	2080	2345	2615	2885	3120	3350
65	1720	1975	2265	2555	2850	3140	3395	3650
50	1805	2075	2380	2685	2995	3300	3570	3835
40	1880	2160	2480	2800	3120	3440	3720	4000
25	2040	2340	2685	3035	3380	3725	4030	4330
10	2575	2960	3395	3835	4275	4710	5095	5475

Printed on 06/12/2023 22:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..