

AGRIMAX SIRIO - Ficha técnica



Description

AGRIMAX SIRIO es un neumático para las altas velocidades (hasta 70 km/h) desarrollado por BKT para equipar los tractores de elevada potencia. El dibujo es perfecto para las aplicaciones de transporte y tratamiento del terreno. La elevada flexibilidad del flanco asegura una estabilidad, manutención y confort extraordinarios, mejorando la experiencia de conducir. Esta también disponible con tecnología IF permitiendo el transporte de cargas pesadas a baja presión. La carcasa reforzada y el número alto de cinturones garantizan una excelente tracción en el campo, mientras que la baja resistencia al rodamiento contribuye a un consumo menor de carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 R 30	HIGH SPEED	94045310	R1W	150 D/147 E	W 16 L	W 18	20.9	57.6	26.3	173.2	TL	E4-106R-000814
IF 600/70 R 30	HIGH SPEED	94044849	R1W	165 D/162 E	DW 21 B	DW 20 B	23.7	63.1	28.1	187.4	TL	E4-106R-000817
540/65 R 34	HIGH SPEED	94045297	R1W	152 D/149 E	W 16 L	W 18	20.9	61.7	28.4	186.4	TL	E4-106R-000815
540/65 R 38	HIGH SPEED	94044290	R1W	153 D/150 E	W 16 L	W 18 L	20.9	65.6	30.3	198.8	TL	E4-106R-000816
710/70 R 38	HIGH SPEED	94044283	R1W	171 D/168 E	DW 23 B	DW 25 B	28.2	77.1	34.9	229.9	TL	E4-106R-000818

Printed on 03/12/2023 14:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..