

AGRIMAX TERIS - Especificaciones técnicas



Description

Las actuales cosechadoras de elevada potencia requieren neumáticos capaces de soportar máquinas y cargas pesadas sin dañar los cultivos. BKT se compromete a ofrecer las soluciones de neumáticos radiales a la vanguardia para aumentar el rendimiento de su cosecha. AGRIMAX TERIS es el compañero ideal para sus operaciones combinadas. Excelente tracción y elevada capacidad de carga son las dos características fundamentales que se traducen en el mejor rendimiento para todas las operaciones de la cosecha. La protección del flanco y el hombro redondeado incrementan la resistencia – alargando el ciclo de vida del producto – incluso en condiciones adversas aunque hay los rastros en el campo.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Cosechadora de algodón • Cosechadora

Version	STANDARD
Type	TL
Tyre Size	IF 710/75 R 34 CFO
LI/SS	184 A8/B

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	1930
Static Loaded Radius (mm)	870
Rolling Circumference (mm)	5852
SRI (mm)	900
Rim Rec	DW 25 B
ECE	E11-106R-004899

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	3510	4050	4590	5220	5760	6390	7110	7650	8370	9000
40	3510	4050	4590	5220	5760	6390	7110	7650	8370	9000
30	3760	4335	4915	5590	6165	6840	7610	8190	8960	9630
15 Cyc*	5795	6685	7575	8615	9505	10545	11735	12625	13815	14850
10 Cyc*	6320	7290	8265	9400	10370	11505	12800	13770	15070	16200

* - * For 15 & 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 23/04/2024 7:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..