

## AGRIMAX TURF RT 333 - Especificaciones técnicas



### Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Maquina para la recogida de fruta •  
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	200/70 R 16
LI/SS	94 A8/B

## Dimensions International Standard

Section Width (mm)	200
Overall Diameter (mm)	686
Static Loaded Radius (mm)	317
Rolling Circumference (mm)	2054
SRI (mm)	330
Rim Rec	W 6
ECE	E11-106R-008659
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	315	365	420	470	525	580	625	670
40	315	365	420	470	525	580	625	670
30	340	390	450	505	565	620	670	720
10 LT	425	490	560	630	705	775	840	900
10 HT	340	390	450	505	565	620	670	720

Printed on 12/04/2024 22:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..