

## AGRIMAX TURF RT 333 - Especificaciones técnicas



### Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Maquina para la recogida de fruta •  
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	240/60 R12
LI/SS	89 A8/B

## Dimensions International Standard

Section Width (mm)	242
Overall Diameter (mm)	592
Static Loaded Radius (mm)	269
Rolling Circumference (mm)	1777
Rim Rec	W7
ECE	E11-106R-007679

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	270	310	355	395	445	485	540	580
40	270	310	355	395	445	485	540	580
30	290	335	385	425	475	520	585	625
10 LT	360	415	480	535	595	650	730	780
10 HT	290	335	385	425	475	520	585	625

Printed on 27/04/2024 16:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..