

## AGRIMAX TURF RT 333 - Especificaciones técnicas



### Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Maquina para la recogida de fruta •  
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	240/70 R16
LI/SS	104 A8/B

## Dimensions US Standard

Usa code	94070282
Section Width (inch)	9.6
Overall Diameter (inch)	29.2
Static Loaded Radius (inch)	13.4
Rolling Circumference (inch)	87.1
Rim Rec	W8
Rim Alt	W 8 L ; W 9
ECE	E11-106R-007531

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	940	1090	1240	1390	1560	1710	1880	1990
25	940	1090	1240	1390	1560	1710	1880	1990
20	1010	1160	1330	1500	1670	1830	2010	2130
5 LT	1260	1450	1670	1880	2090	2310	2520	2670
5 HT	1010	1160	1330	1500	1670	1830	2010	2130

Printed on 12/04/2024 22:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..