

AGRIMAX TURF RT 333 - Especificaciones técnicas



Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Maquina para la recogida de fruta •
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	280/70 R 18
LI/SS	114 A8/114 B

Dimensions US Standard

Usa code	94065707
Section Width (inch)	11.4
Overall Diameter (inch)	33.1
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	100.4
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E11-106R-006473

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1230	1420	1630	1830	2040	2240	2450	2610
25	1230	1420	1630	1830	2040	2240	2450	2610
20	1320	1520	1740	1970	2190	2410	2630	2790
5 LT	1650	1900	2180	2450	2740	3010	3290	3500
5 HT	1320	1520	1740	1970	2190	2410	2630	2790

Printed on 27/04/2024 22:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..