

## AGRIMAX TURF RT 333 - Especificaciones técnicas



### Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Maquina para la recogida de fruta •  
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	320/70 R 20
LI/SS	113 A8/113 B

## Dimensions US Standard

Usa code	94067558
Section Width (inch)	12.6
Overall Diameter (inch)	38.7
Static Loaded Radius (inch)	17.4
Rolling Circumference (inch)	114.8
Rim Rec	W10
Rim Alt	W9 ; W11
ECE	E11-106R-006944

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1400	1640	1860	2090	2320	2540
25	1400	1640	1860	2090	2320	2540
20	1500	1760	2000	2240	2490	2370
5 LT	1880	2190	2500	2800	3110	3410
5 HT	1500	1760	2000	2240	2490	2370

Printed on 12/04/2024 23:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..