

AGRIMAX TURF RT 333 - Especificaciones técnicas



Description

El AGRIMAX TURF RT 333 (R-3+) es un neumático radial diseñado para pequeños tractores utilizados para aplicaciones de jardinería, viñedos y huertos. Su diseño de hombro redondeado ofrece una baja compactación del suelo y lo hace extremadamente delicado sobre el terreno. Su exclusiva banda de rodadura extraprofunda (R-3+) y el diseño especial con bloques direccionales ofrecen una excelente tracción tanto en el campo como en carretera, así como una mayor duración del ciclo de vida útil del neumático. El AGRIMAX TURF RT 333 (R-3+) garantiza unas magníficas propiedades de autolimpieza y, gracias a su reducida resistencia a la rodadura, permite un significativo ahorro de combustible.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Maquina para la recogida de fruta •
Minitractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	420/70 R 24
LI/SS	130 A8 / 130 B

Dimensions International Standard

Section Width (mm)	418
Overall Diameter (mm)	1248
Static Loaded Radius (mm)	557
Rolling Circumference (mm)	3728
SRI (mm)	575
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-007206

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1045	1220	1390	1560	1730	1900
40	1045	1220	1390	1560	1730	1900
30	1120	1305	1490	1670	1855	2035
10 LT	1405	1635	1865	2095	2325	2550
10 HT	1120	1305	1490	1670	1855	2035

Printed on 13/04/2024 0:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..