

AGRIMAX V-FLECTO - Especificaciones técnicas



Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafiante en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la innovadora tecnología VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	SPECIAL
Type	TL
Tyre Size	VF 710/60 R 46 CFO
LI/SS	174 D

Dimensions International Standard

Section Width (mm)	715
Overall Diameter (mm)	2041
Static Loaded Radius (mm)	896
Rolling Circumference (mm)	6092
SRI (mm)	975
Rim Rec	DW 25 B
Rim Alt	DW 27 B
Narrow Rim option	DW 20 B
ECE	E11-106R-0011234
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
70	3355	3905	4455	5005	5555	6100
from 65 to 40	3685	4290	4895	5495	6100	6700
30	3760	4375	4990	5605	6220	6835
20	3835	4465	5090	5720	6345	6970
10	4055	4720	5385	6045	6710	7370
Upto 30 Cyc	4185	4870	5555	6240	6925	7605
Upto 15 Cyc	4995	5815	6630	7450	8265	9080
Upto 10 Cyc	5475	6370	7265	8160	9055	9950
10HT	3760	4375	4990	5605	6220	6835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 2:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..