

AGRIMAX V-FLECTO - Especificaciones técnicas



Description

AGRIMAX V-FLECTO es la respuesta de BKT a la demanda desafiante en clave de la tecnología y las prestaciones de los tractores de elevada potencia. Este neumático es perfecto para aplicaciones de tratamiento del terreno y de transporte gracias a una menor compactación del suelo. Con la innovadora tecnología VF, AGRIMAX V-FLECTO permite transportar cargas pesadas con una presión de inflado inferior en comparación con un neumático estándar o IF, alcanzando velocidades elevadas. Presenta l'Opción de Llanta Estrecha (NRO) que permite el montaje de llantas estándar. BKT ha diseñado este neumático con una geometría optimizada que incrementa el confort de conducción en el campo y por carretera reduciendo el consumo de carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor de alta potencia

Version	SPECIAL
Type	TL
Tyre Size	VF 900/60 R 42 CFO
LI/SS	189 D

Dimensions International Standard

Section Width (mm)	900
Overall Diameter (mm)	2142
Static Loaded Radius (mm)	937
Rolling Circumference (mm)	6390
SRI (mm)	1025
Rim Rec	DW 30B
Narrow Rim option	DW 28 B
ECE	E11-106R-006165

Load capacity (Kg)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2
70	4590	5340	6180	6930	7680	8435	9370
from 65 to 40	5045	5870	6795	7620	8445	9270	10300
30	5145	5985	6930	7770	8610	9455	10505
20	5245	6100	7065	7920	8780	9640	10710
10	5545	6455	7470	8380	9285	10195	11330
Upto 30 Cyc	5730	6665	7720	8655	9590	10525	11690
Upto 15 Cyc	6840	7955	9215	10330	11445	12560	13955
Upto 10 Cyc	7495	8720	10095	11320	12545	13770	15295
10 HT	5145	5985	6930	7770	8610	9455	10505

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 3:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..