

AIROMAX AM 27 - Especificaciones técnicas



Description

AIROMAX AM 27 es un neumático que se utiliza principalmente por carretera, ideal para las aplicaciones con grúas en el sector de la construcción. Este neumático se caracteriza por su resistencia al calor y excepcional confort. AIROMAX AM 27 es un neumático para utilizarlo con una alta velocidad, particularmente idóneo para todas las operaciones que requieran un elevado nivel de maniobrabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Grúa móvil

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 445/95 R 25 (16.00 R 25) |
| LI/SS | 174 F |

Dimensions International Standard

| | |
|----------------------------|-----------------------------|
| Overall Width (mm) | 440 |
| Overall Diameter (mm) | 1490 |
| Static Loaded Radius (mm) | 695 |
| Rolling Circumference (mm) | 4587 |
| Rim Rec | 11.25/2.0 |
| Rim Alt | 11.00/1.7 CR ; 11.00/1.7CRL |
| ECE | E4-54R-0028867 |

Load capacity (Kg)

| km/h / bar | 9.00 |
|------------|------|
| 30 | 8500 |
| 40 | 7750 |
| 50 | 7500 |
| 60 | 7300 |
| 70 | 7100 |
| 80 | 6700 |
| 90 | 6300 |
| 100 | 5600 |

Printed on 19/04/2024 20:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..