

AIROMAX AM 543 - Especificaciones técnicas



Description

AIROMAX AM 543 es el neumático ideal para las grúas que se utilizan en el sector de la construcción. Este neumático presenta una excelente tracción, así como una elevada estabilidad. Visto que los neumáticos para grúas están sometidos a solicitaciones y condiciones de empleo extremas, AIROMAX AM 543 ha sido proyectado para proporcionar una óptima resistencia al calor. Además, es idóneo para todas las operaciones en las que se requiere un elevado nivel de maniobrabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Grúa móvil

Version	STANDARD
Type	TT
Tyre Size	385/95 R 24 (14.00 R 24)
LI/SS	170 E

Dimensions International Standard

Overall Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4156
Rim Rec	10.00W

Load capacity (Kg)

km/h / bar	9.00
70	6000

Printed on 17/04/2024 5:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..