

ARROW - Especificaciones técnicas



Description

ARROW es idóneo para las aplicaciones de transporte con remolques. Este neumático ha sido desarrollado para utilizarlo principalmente por carretera y asegura un mayor kilometraje y una vida operativa más larga. ARROW ofrece elevada capacidad de carga incluso a altas velocidades. Está disponible también como versión HD que asegura un rendimiento optimizado.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Version	TRACTOR TRAILER
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	270
Overall Diameter (mm)	1040
Rim Rec	7.0
Rim Alt	6.5 ; 7.5

Load capacity (Kg)

km/h / bar	7.25
40	2715

Printed on 27/04/2024 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..