

AS 504 - Especificaciones técnicas



Description

AS 504 es un neumático agro-industrial desarrollado principalmente para los trabajos del campo y aplicaciones con maquinaria agrícola y en la manipulación de materiales. Este neumático, caracterizado por excelentes propiedades de auto limpieza y agarre potenciado, es idóneo para los remolques en el campo y los elevadores telescópicos. Hay disponibles varias versiones del neumático AS 504 para satisfacer las diferentes exigencias específicas del usuario: una versión "HD" con una mezcla especial resistente a los cortes y los desgarres, mientras que la versión "special" está realizada con una carcasa reforzada que asegura una vida más larga del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Elevador telescópico • Ewamolque para campos
Industrial: Elevador telescópico

Version	STANDARD
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	145 A8
LI/SS FREE ROLLING	157 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	384
Overall Diameter (mm)	1262
Static Loaded Radius (mm)	570
Rolling Circumference (mm)	3875
SRI (mm)	600
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L
ECE	E11-106R-003574

Load capacity (Kg)

	km/h / bar	3.00
	10 FR	5775
	25 FR	4910
	30 FR	4620
	40 FR	4125
	10 DW	4060
	25 DW	3450
	30 DW	3250
	40 DW	2900

Printed on 23/04/2024 18:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..