

AS 504 - Especificaciones técnicas



Description

AS 504 es un neumático agro-industrial desarrollado principalmente para los trabajos del campo y aplicaciones con maquinaria agrícola y en la manipulación de materiales. Este neumático, caracterizado por excelentes propiedades de auto limpieza y agarre potenciado, es idóneo para los remolques en el campo y los elevadores telescópicos. Hay disponibles varias versiones del neumático AS 504 para satisfacer las diferentes exigencias específicas del usuario: una versión "HD" con una mezcla especial resistente a los cortes y los desgarres, mientras que la versión "special" está realizada con una carcasa reforzada que asegura una vida más larga del neumático.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Elevador telescópico • Ewamolque para campos
Industrial: Elevador telescópico

Version	STANDARD
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	148 A8
LI/SS FREE ROLLING	160 A8

Dimensions US Standard

Usa code	94018987
Ply Rating	14
Section Width (inch)	15.1
Overall Diameter (inch)	49.7
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	152.6
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-002816

Load capacity (lbs)

mph / psi	51
5 FR	13890
15 FR	11810
20 FR	11110
25 FR	9920
5 DW	9720
15 DW	8270
20 DW	7780
25 DW	6940

Printed on 23/04/2024 17:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..