

# AS 504 - Especificaciones técnicas



## Description

AS 504 es un neumático agro-industrial desarrollado principalmente para los trabajos del campo y aplicaciones con maquinaria agrícola y en la manipulación de materiales. Este neumático, caracterizado por excelentes propiedades de auto limpieza y agarre potenciado, es idóneo para los remolques en el campo y los elevadores telescópicos. Hay disponibles varias versiones del neumático AS 504 para satisfacer las diferentes exigencias específicas del usuario: una versión "HD" con una mezcla especial resistente a los cortes y los desgarres, mientras que la versión "special" está realizada con una carcasa reforzada que asegura una vida más larga del neumático.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agricultura: Elevador telescópico • Ewamolque para campos  
Industrial: Elevador telescópico

Version	STANDARD
Type	TT
Tyre Size	5.00 - 15
LI/SS DRIVE WHEEL	67 A8
LI/SS FREE ROLLING	79 A8

## Dimensions US Standard

Usa code	94019144
Ply Rating	4
Section Width (inch)	5.5
Overall Diameter (inch)	25.9
Static Loaded Radius (inch)	12.1
Rolling Circumference (inch)	77
Rim Rec	3.50 D
Rim Alt	3.00 D ; 4.00 E ; 4 J
ECE	E11-106R-004237

## Load capacity (lbs)

mph / psi	33
5 FR	1340
15 FR	1150
20 FR	1070
25 FR	960
5 DW	940
15 DW	800
20 DW	750
25 DW	670

Printed on 23/04/2024 17:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..