

## AS 505 - Ficha técnica



### Description

AS 505 es ideal para trabajar en el campo con remolques y maquinaria agrícola. Este neumático se caracteriza por sus óptimas propiedades de auto limpieza, así como por una mayor tracción en el terreno, especialmente en los fangosos. Este neumático asegura un amplio ciclo de vida del producto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Maquinaria agrícola • Remolque

| SIZE        | Version  | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT          | SW  | OD  | SLR | RC   | Type | ECE            |
|-------------|----------|-------------------|--------------------|----|---------|------------------|-----|-----|-----|------|------|----------------|
| 6.5/80 - 15 | STANDARD | 92 A8             | 104 A8             | 8  | 5.0     | 4½ K ; 5 K ; 5 J | 171 | 695 | 325 | 2106 | TL   | E4-106R-002660 |
| 6.5/80 - 15 | STANDARD | 86 A8             | 98 A8              | 6  | 5.0     | 4½ K ; 5 K ; 5 J | 171 | 695 | 325 | 2106 | TL   | E4-106R-002188 |

Printed on 30/01/2023 17:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..