

## AT 108 - Especificaciones técnicas



### Description

AT 108 es un neumático todo terreno para vehículos ATV. El dibujo de la banda de rodadura asegura un confort excelente y prestaciones dentro y fuera de las carreteras.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Vehículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 20 X 10 - 10

## Dimensions US Standard

Usa code	94034499
Ply Rating	4
Section Width (inch)	9.8
Overall Diameter (inch)	20.2
Static Loaded Radius (inch)	9.3
Rolling Circumference (inch)	56.1
Rim Rec	8.0 AT
Rim Alt	7.5 AT ; 8.5 AT
ECE	E11-75R-004567

## Load capacity (lbs)

	mph / psi	5
	62	260

Printed on 20/04/2024 3:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..