

# AT 109 - Ficha técnica



## Description

AT 109 es un neumático todo terreno para vehículos ATV. El dibujo de la banda de rodadura asegura una excelente protección del campo.

### UM

International Standard

#### Construction

BIAS

**Machinery** Agricultura: Vehículo ATV

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Туре	ECE
AT 145 X 70 - 6	STANDARD	2	4.5		137	366	TL	
AT 16 X 8 - 7	STANDARD	2	6.5 AT	6.0 AT	183	419	TL	
AT 18 X 9.5 - 8	STANDARD	2	7.5 AT	8.0 AT	220	468	TL	E11-75R-004668
AT 20 X 7 - 8	STANDARD	2	5.5 AT	6.0 AT	170	504	TL	E11-75R-004669
AT 21 X 9 - 8	STANDARD	2	7.0 AT	6.5 AT ; 7.5 AT	222	536	TL	
AT 22 X 11 - 8	STANDARD	2	9.0 AT	8.5 AT	230	579	TL	E11-75R-004670
AT 25 X 12 - 9	STANDARD	2	9.5 AT	9.0 AT ; 10.0 AT	269	617	TL	E11-75R-004671

#### Printed on 05/05/2024 10:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..