

AT 111 HD - Especificaciones técnicas



Description

AT 111 HD es idóneo para las aplicaciones deportivas todo terreno con vehículos ATV. La profundidad incrementada y el fuerte espesor de los flancos ofrecen una extrema adherencia y control de frenado, junto a una excelente tracción y control con altas velocidades y en las maniobras de sobreviraje. AT 111 HD asegura un largo ciclo de vida del neumático.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Vehículo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 22 X 11 - 9

Dimensions International Standard

Ply Rating	6
Section Width (mm)	279
Overall Diameter (mm)	560
Rim Rec	9.0 AT
Rim Alt	8.5 AT
ECE	E4-75R-0006332

Load capacity (Kg)

km/h / bar	0.45
100	180

Printed on 20/04/2024 16:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..