

AT 603 - Especificaciones técnicas



Description

AT 603 es un neumático agro-industrial para maquinaria agrícola y las ternas. AT 603 ha sido proyectado para asegurar una excelente tracción en la rueda motriz, proporcionando óptimas prestaciones en todas las superficies, así como optimas propiedades de auto-limpieza. AT 603 está disponible en una versión "especial" con carcasa reforzada, mientras que la versión "HD" ofrece una mayor resistencia a los cortes y los desgarros.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Cargadora retroexcavadora • Maquinaria agrícola

Industrial: Cargadora retroexcavadora

Version	SPECIAL
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions US Standard

Usa code	94019670
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	107.4
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E11-106R-004546

Load capacity (lbs)

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Printed on 25/04/2024 9:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..