

## AT 603 - Especificaciones técnicas



### Description

AT 603 es un neumático agro-industrial para maquinaria agrícola y las ternas. AT 603 ha sido proyectado para asegurar una excelente tracción en la rueda motriz, proporcionando óptimas prestaciones en todas las superficies, así como optimas propiedades de auto-limpieza. AT 603 está disponible en una versión "especial" con carcasa reforzada, mientras que la versión "HD" ofrece una mayor resistencia a los cortes y los desgarros.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Cargadora retroexcavadora • Maquinaria agrícola

Industrial: Cargadora retroexcavadora

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	274
Overall Diameter (mm)	907
Static Loaded Radius (mm)	422
Rolling Circumference (mm)	2727
SRI (mm)	425
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E4-106R-002325

## Load capacity (Kg)

	km/h / bar	3.70
	10 FR	2730
	25 FR	2320
	30 FR	2185
	40 FR	1950
	10 DW	1905
	25 DW	1620
	30 DW	1525
	40 DW	1360

Printed on 25/04/2024 10:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..