

AW 09 - Especificaciones técnicas



Description

AW 09 ha sido desarrollado para la maquinaria agrícola, las empacadoras de heno y los remolques que se utilizan en los trabajos del campo, en la cosecha de heno y en el transporte. Es idóneo para utilizarlo en la agricultura moderna tanto por carretera como fuera de la carretera. Su carcasa reforzada garantiza elevada capacidad de carga y una vida operativa más larga. AW 09 está realizado con una mezcla de la banda de rodadura resistente a las perforaciones que fornece una excelente resistencia a los rastros insidiosos.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Cosechadora •
Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	120 A8
LI/SS FREE ROLLING	132 A8

Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	860
Static Loaded Radius (mm)	376
Rolling Circumference (mm)	2520
Rim Rec	9.00
ECE	E4-106R-000375

Load capacity (Kg)

	km/h / bar	2.80
	10 FR	2800
	25 FR	2380
	30 FR	2240
	40 FR	2000
	10 DW	1960
	25 DW	1665
	30 DW	1570
	40 DW	1400

Printed on 27/04/2024 8:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..