

## AW 705 - Especificaciones técnicas



### Description

AW 705 ha sido desarrollado para maquinaria agrícola, remolques y empacadoras de heno que se utilizan en los trabajos del campo y en el transporte. Es idóneo para utilizarlo en la agricultura moderna gracias a durabilidad superior y una capacidad de carga elevada.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20
LI/SS FREE ROLLING	151 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	408
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3155
Rim Rec	13.0
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002711

## Load capacity (Kg)

km/h / bar	3.00
10 FR	4830
25 FR	4105
30 FR	3865
40 FR	3450

Printed on 26/04/2024 9:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..