

AW 708 - Especificaciones técnicas



Description

AW 708 ha sido desarrollado para trabajar en el campo y en las aplicaciones de transporte y recogida de heno con maquinaria agrícola, remolques y empacadoras de paja. AW 708 está disponible en una versión realizada con una mezcla especial resistente a los cortes y los desgarres.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola •
Remolque
Industrial: Remolque

Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	148 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	470
Overall Diameter (mm)	866
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2536
Rim Rec	16.00
ECE	E4-106R-002268

Load capacity (Kg)

	km/h / bar	3.30
	10 FR	4410
	25 FR	3750
	30 FR	3530
	40 FR	3150

Printed on 17/04/2024 5:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..