

## AW 726 - Especificaciones técnicas



### Description

AW 726 ha sido particularmente desarrollado para remolques en las aplicaciones de transporte. Este neumático es idóneo para utilizarlo tanto por la carretera como fuera de la carretera. AW 726 asegura óptimas prestaciones en la carretera y una excelente auto-limpieza. El dibujo con bloques asegura un amplio ciclo de vida del producto.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

## Dimensions US Standard

Usa code	94053698
Ply Rating	14
Section Width (inch)	11.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	14.3
Rolling Circumference (inch)	99.6
Rim Rec	9.00
ECE	E11-106R-005264

## Load capacity (lbs)

mph / psi	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 10:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..