

AW 726 - Especificaciones técnicas



Description

AW 726 ha sido particularmente desarrollado para remolques en las aplicaciones de transporte. Este neumático es idóneo para utilizarlo tanto por la carretera como fuera de la carretera. AW 726 asegura óptimas prestaciones en la carretera y una excelente auto-limpieza. El dibujo con bloques asegura un amplio ciclo de vida del producto.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Remolque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensions US Standard

Usa code	94054008
Ply Rating	18
Section Width (inch)	15.7
Overall Diameter (inch)	34.4
Rim Rec	AG 13.00
ECE	E11-106R-005341

Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160
5 DW	7100
15 DW	6030
20 DW	5680
25 DW	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/06/2025 3:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..