

## AW 729 - Especificaciones técnicas



### Description

El AW 729 es un neumático agrícola diseñado específicamente para aplicaciones de transporte, cosecha de heno, empaçado y labranza de tierras. Su diseño de hombro redondeado y banda de rodadura con tres surcos centrales proporciona una baja compactación del suelo y evita daños en el campo.

El AW 729 es el neumático ideal para la agricultura moderna y es adecuado tanto para usarse tanto en carretera como fuera de ella.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricultura: Empacadora de heno • Maquinaria agrícola • Remolque

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	385
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2560
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E11-106R-008727

## Load capacity (Kg)

km/h / bar	2.60
10 FR	2970
25 FR	2520
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Printed on 23/04/2024 14:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..