

BK 208 - Especificaciones técnicas



Description

BK 208 es idóneo para su empleo en remolques y camionetas. Es un neumático especialmente duradero y fiable para utilizarlo tanto en el campo como por la carretera.

UM

US Standard

Construction

 BIAS

Machinery

Agricultura: Tractor compacto • Camión ligero • Remolque

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 7.50 - 16 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94013258 |
| Ply Rating | 16 |
| Section Width (inch) | 8.3 |
| Overall Diameter (inch) | 31.9 |
| Rim Rec | 6.00 G |

Load capacity (lbs)

| | mph / psi | - |
|---|-----------|---|
| - | - | - |
| - | - | - |

Printed on 13/04/2024 12:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..