

## BK 4040 - Ficha técnica



### Description

BK 4040 está principalmente proyectado para remolques agrícolas en las aplicaciones de transporte. Su robusta carcasa proporciona una elevada capacidad de carga y una durabilidad superior.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricultura: Remolque

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
6.50 - 16	STANDARD	94044146	10	4.50 E		7.2	29.1	TT	E11-106R-005299
7.00 - 16	STANDARD	94044481	12	5.50	5.00 F	7.8	30.3	TT	E11-106R-005300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 6:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..