

## BK 6060 - Especificaciones técnicas



### Description

BK 6060 es un neumático idóneo para utilizarlo tanto en el campo como por la carretera, desarrollado especialmente para remolques y cargadoras retroexcavadoras en las aplicaciones de transporte y para las operaciones de excavación y carga. El dibujo de bloques en la banda de rodadura garantiza un ciclo de vida prolongado del neumático.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Industrial: Cargadora retroexcavadora • Remolque

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

## Dimensions US Standard

Usa code	94027323
Ply Rating	16
Section Width (inch)	10
Overall Diameter (inch)	36.4
Static Loaded Radius (inch)	16.8
Rolling Circumference (inch)	107.9
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

## Load capacity (lbs)

mph / psi	105
20	5070

Printed on 25/04/2024 21:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..