

## BK 6060 - Ficha técnica



### Description

BK 6060 es un neumático idóneo para utilizarlo tanto en el campo como por la carretera, desarrollado especialmente para remolques y cargadoras retroexcavadoras en las aplicaciones de transporte y para las operaciones de excavación y carga. El dibujo de bloques en la banda de rodadura garantiza un ciclo de vida prolongado del neumático.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Cargadora retroexcavadora • Remolque

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	INDUSTRIAL	16	6.50 H	6.00 G	255	925	427	2740	TT	E11-106R-004362

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 18:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..